

SUPER-TRONIC 15W-40 CI-4/SL

A premium heavy duty diesel engine oil, formulated with todays sophisticated electronic engines in mind Meeting or exceeding most of nearly all modern engine manufacturers and OEM'S requirements.

- # API CI-4/SL
- # ACEA E2-96,ISSUE 2
- # ACEA A3-98,B3 -98
- # Cummins 20071&20076
- # DDC series 2000/4000 Type 1
- #Caterpillar TO-2
- #Mack EO-M, EO-M plus
- #Man 271
- # Mercedes-Benz sheet 228.1,229.1
- # MTU Type 1
- # VOLVO VDS, VDS-2 # VW 501
- # Allison C4

An ideal application for all fleet diesel engines, can be used in earthmoving equipment, road & transport applications, stationary engines as well as light commercial diesel and Allison C4 Transmissions. Offering sludge and soot control for a cleaner engine, reducing oil consumption and greatly reducing engine wear offering extended engine life, providing fuel saving. Extremely good low temperatures viscometrics for reduced wear at start up.

TYPICAL CHARACTERISTICS	UNIT	VALUE
PROPERTIES		
SAE GRADE		15W40
VISCOSITY @40o	cST	91
VISCOSITY @100o	cST	13.8
FLASH POINT	C	210
POUR POINT	C	-30