

# ATLANTIC PRO DIESEL 15W-40CJ-4/SM

## PRODUCT DESCRIPTION

ATLANTIC PRO DIESEL low SAPS (Sulfated Ash, Phosphorus and Sulfur) technology SAE 15W-40 diesel engine oil is specially formulated to extend engine oil drain intervals and provide high soot dispersion in modern diesel engines. It is formulated to improve engine durability in the latest emissions controlled heavy duty diesel engines.

## PRODUCT APPLICATIONS

ATLANTIC PRO DIESEL is recommended for 2008 model engines and can also be used in most petrol engines.

## TYPICAL CHARACTERISTICS

ATLANTIC PRO DIESEL is recommended where these current or superseded specifications or performance levels are cited:

API:	Diesel/Petrol Rating CJ-4, CI-4 Plus, CI-4, (also CH-4, CG-4, CF-4, CE and CD)/SL.
ACEA:	E5 & E7
VOLVO:	VDS-4 approved
MACK:	EC-O Premium Plus (also suitable for EO-N PP, EO-M Plus, EO-M, EO-L Plus, EO-L, EO-K, EO-K2)
Cummins:	CES 20081
Caterpillar:	ECF-3
Detroit:	DDC Power Guard 93K218 approved
Mercedes Benz:	228.31
JASO:	DH-2

SAE Viscosity Grade	KV @ 40 °C (cSt)	KV @ 100 <sup>0</sup> (cSt)	CCS @ -20 °C (cP)	Viscosity Index	Pour Point (°C)	Closed Flash Point (°C)	Sulphated Ash % Mass	TBN mg KOH/g
15W-40	114.6	14.8	6200	133	-33	>200	0.99	8.62