

# ATLANTIC QIK-SHIFT 6

## Product Description

ATLANTIC QIK-SHIFT 6 is an automatic transmission fluid specially formulated and approved for the latest General Motors Dexron® VI, GMN 10060 specification. It supersedes all previous Dexron® fluids for General Motors Holden applications.

ATLANTIC QIK-SHIFT 6, GMN 10060 specification supersedes earlier Dexron® specifications - Dexron® III H, G, F; Dexron® II E, D and Dexron® fluids in all GM automatic transmissions. These include hydramatic and automatic transmissions in Holden, Chevrolet, Pontiac, Buick, etc.

## Product Application

ATLANTIC QIK-SHIFT 6 automatic transmission fluid (ATF) is a synthetic-based automatic transmission fluid meeting the requirements of the General Motors' DEXRON® VI specification. ATLANTIC QIK-SHIFT 6® VI is fully backwards compatible and can be used whenever DEXRON® II and/or DEXRON® III are recommended in GM/Holden vehicles and transmissions.

ATLANTIC QIK-SHIFT 6 is recommended for all transmissions used in General Motors cars, Holden, Isuzu, Opel and Hydramatic transmissions used in a range of vehicles. ATLANTIC QIK-SHIFT 6 may be used in power steering for the majority of cars, light commercial vehicles and tractors except where specialist fluids are recommended; e.g., Honda, Mercedes-Benz, SAAB. This product is not suitable where Ford M2C-33 is recommended.

ATLANTIC QIK-SHIFT 6 is recommended for automatic transmissions of the following vehicles:

- Imported GM vehicles 2006 onwards.
- Holden Commodore VE onwards.
- Holden Statesman, Caprice six speed transmissions.
- Suitable for many hydraulic systems where ISO 22 or 32 Hydraulic Oils or SAE 10W engine oils are recommended.

## Product Features & Benefits

- Enhances the performance of new and older GM transmissions.
- Provides consistent shift performance to allow for longer service intervals.
- Extended transmission fluid life and resists fluid breakdown at higher operating temperatures.
- Provides excellent oxidative stability under severe conditions.
- Provides friction stability and durability combined with excellent wear protection
- Excellent durability for taxis, vehicles used for towing and other hard working applications.
- Reduces sludge and varnish build up.
- Protects transmission gears and allows them to operate smoothly.
- Maintains lubricity
- Flows well for cold start-up.

### Typical Characteristics

SAE Viscosity Grade	Specific Gravity @ 15°C	Viscosity @ 100°C (cSt)	Viscosity @ 40°C (cSt)	Pour Point (°C)	Colour	Flash point °C (PMCC)
0W-20	0.850	6.0	30	<-45	Red	200

### Performance Levels

Dexron® VI is suitable and recommended in General Motors, Holden, Chevrolet, Pontiac, Hydramatic etc, where the following performance levels are specified:

Dexron® VI, III H, G and F, Dexron® II E and D, Dexron®, Type A Suffix  
Holden HN 2126 Power steering systems of GM vehicles specifying Dexron® fluids.

Currently Dexron® VI fluids are not recommended for most non-General Motors automatic transmissions. For non-GM automatic transmissions that recommend Dexron® fluids, Atlantic recommends QIK-SHIFT DEXRON III or ATLANTIC MER-CON 5. Please consult vehicle service manuals.

# ATLANTIC