

ATLANTIC OPTIMUM ULTRA

5W-40 SM/CF

5W-50 SM/CF

ATLANTIC OPTIMUM ULTRA High Performance Synthetic Engine Oil is an advanced Fully Synthetic formulation recommended for applications specifying API/ SM/CF. Suitable for passenger cars, MPVs, SUVs, light-duty diesel engines and turbocharged gasoline engines. ATLANTIC OPTIMUM ULTRA High Performance Synthetic Engine Oil performs exceptionally well in demanding frequent stop and go, city driving conditions.

ATLANTIC OPTIMUM ULTRA High Performance Synthetic Engine Oil in grade SAE5W-50 also meets the specification of ACEA A3. In grade SAE5W-40, ATLANTIC OPTIMUM ULTRA High Performance Synthetic Engine Oil meets the following additional specifications:

- ACEA A3-98, A3-02, B3-98, B4-02
- BMW "Long life Engine Oils"
- MB 229.1, 229.3 approved
- VW 502, 505 approved
- Porsche approved

TYPICAL PROPERTIES

SAE Grade	5W-40	5W-50	
Gravity °API	35	34.6	
Pour Point °C	-33	-33	
Flash Point (COC) °C	228	223	
Viscosity			
	cSt at 40°C	92	116
	cSt at 100°C	14.3	18.2
Color ASTM	L2.5	L2.5	
Viscosity Index	160	175	